

TUBE WALL IP INDOOR / OUTDOOR

LED 10+10W / 20+20W / 25+25W **85 lm/W**



Características mecánicas Mechanical specifications




Material del cuerpo: aluminio fundido
Housing material: cast aluminum

Material del difusor: policarbonato
Diffuser material: polycarbonate

Color: Blanco, Negro, Plata
Colour: Black, White, Silver



Tamaño: 3 tamaños según potencia
Size: 3 sizes according to power

Basculación: NO
Tilting:





Pared
Wall



10+10W



20+20W



25+25W



Características ópticas Optical specifications

LED: CREE CXB Series

Potencias: 10+10W / 20+20W / 25+25W
Power

Flujo luminoso: de 850 lm a 2275 lm
Luminous flux: from 850 lm to 2275 lm

Eficacia: 85 lm/W
Efficacy

IRC (CRI): >80 >90

Temperatura de color: 2700K - 6500K
Color temperature

Ángulo de apertura: 15° / 40°
Beam angle

Temperatura de trabajo: -20°C +50°C
Work temperature

Vida útil: L70 B20 50.000 h
Lifespan

Características eléctricas Electrical specifications

Driver: Integrado
Driver: Integrated

Voltaje de entrada: 220-240V AC
Input voltage

Frecuencia: 50/60 Hz
Frecuency

Dimmable: Opcional. DALI
Dimmable: Optional. DALI

Acabados Finishing

